



 Facile à installer
Easy to install

Descriptif technique :

Robuste et économe en énergie, le JERSEY est idéal pour l'éclairage des salles machine de moyenne taille. Fixation arrière par vis. Matière : PC et ABS classés UL94 V0 certifiant la non inflammabilité des matériaux. Étanche IP67. Interrupteur et gradateur possibles (01653). Fourni avec 4 vis de fixation et 1 mètre de câble. Longueur de câble supplémentaire disponible en option (réf. 01720). Eclairage de secours 24 VDC disponible (01685, 01686, 01693). Supporte les températures de -25°C à +70°C.

Description :

Its very low consumption and robustness make JERSEY the perfect light for the medium size engine room. Rear fixing by screws. Made in PC and ABS, UL94 V0 very low flammability classified. IP67 waterproof. Switch and dimmer available (01653). Supplied with 4 mounting screws and 1 meter cable. Additional cable length available as an option (ref. 01720). Emergency lighting in 24 VDC available (01685, 01686, 01693). Withstands temperatures from -25°C to +70°C.

	Alim. Voltage	Hertz Hertz	Description Description	Puissance Power	Couleur Colour	Matériau Material	Poids Weight	Angle Angle	Conso. Cons.	Réf. Ref.
	24-30 VDC	-	Plafonnier 10W 10W Downlight	1600 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	290 g	120°	10W	01644
	24-30 VDC	-	Plafonnier 10W avec inter.+gradateur 10W Downlight with switch & dimmer	1600 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	290 g	120°	10W	01653
	24-30 VDC	-	Plafonnier 10W avec secours 10W Downlight with backup	1600 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	290 g	120°	10W	01686
	225-260 VAC	50Hz	Plafonnier 10W 10W Downlight	1600 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	290 g	120°	10W	01643
	225-260 VAC	50Hz	Plafonnier 10W avec secours 10W Downlight with backup	1600 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	290 g	120°	10W	01685
	225-260 VAC	60Hz	Plafonnier 10W 10W Downlight	1600 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	290 g	120°	10W	01692
	225-260 VAC	60Hz	Plafonnier 10W avec secours 10W Downlight with backup	1600 lm	4500 K Blanc neutre 4500 K Neutral white	PC+ ABS PC & ABS	290 g	120°	10W	01693

