

AME-005



Function:

1. Ergonomic design;
2. Seat can move in high strength double-slide rail;
3. Adjustable backrest and headrest;
4. Seat height may be angle adjusted;
5. Seats can be moved back and forth;
6. Folding / angle-adjustable comfortable seat armrest;
7. Seat can rotated 360 degrees, multi-point positioning;
8. Foot pedal height adjustable / folding;
9. Column can be vertically lifting;

Material: 1. Slide rail and positioning base uses the high strength aluminum alloy, inside and outside decorative mosaic made of stainless steel; 2. lifting column with steel, stainless steel synthesis; 3. The seat lifting and tilting, move back and forth, back angle adjusting are used in steel structure; 4. The seat back and the seat cushion adopts the steel inner core and PU cold foam forming disposable sponge synthesis, outsourcing leather or cloth; 5. Steel structure for the footrest; 6. Pneumatic lifting core components pneumatic bar the use of German imports of Stabilus;

Function data: 1. Upper part of the seat can be moved back and forth of 120mm, height adjustment 60mm, seat inclination angle range of $\pm 12^\circ$; 2. Seat backrest with adjustable angle of $85^\circ - 150^\circ$, the headrest adjusted up and down 50mm, handrest multi-point positioning control; 3. The seat of pneumatic lifting regulating range 0-150mm; 4. The seat can rotate 360° and locked, 4-point positioning control; 5. Seat rail slide in 0-4000mm mobile, 500mm rail width and depth 28mm 6. Seat pedal can rotate 90° and regression; 7. Seat can bear more than 150FT.LB torsion, reached AD grade standard;